



Wood Preservative

UPDATE

August 4th, 2023

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com Canada and U.S.A.: dial 1 800 465-7325 Others: dial (514) 523-8324 (Canada)

APPLICATIONS

· For decks, fences, siding, etc. - treated or bare wood - new or old

PROPERTIES

- · Prevents mildew, rot and fungus
- · Penetrating leaves no surface film
- · Releases a strong, potentially persistent odor

DESCRIPTION

Techniseal® Wood Preservative is a clear, penetrating fungicide designed for the protection of new or old untreated wood prior to the application of a sealant, stain, paint or varnish. It is ideal to touch up end cuts on pressure-treated wood, or to fully protect untreated wood. Equally effective on vertical or horizontal surfaces, it extends the life of decks, fences, siding, pergolas, balconies, shingles, docks, etc. Made of zinc naphthenate, Techniseal® Preservative protects wood against mildew, rot and fungus caused by water and dampness.

RESTRICTIONS

Do not apply by spraying or immersion. Use on exterior, aboveground surfaces only. Do not use inside houses. Do not apply to picnic tables; playground accessories or other surfaces that may be in prolonged contact with skin, vegetation, food, feed or drinking water. Do not contaminate drinking or irrigation water sources or aquatic habitats by cleaning tools or by disposing of trash.

DIRECTIONS

BEFORE YOU BEGIN

ALWAYS TEST on a small hidden area of approximately 0.4 m² (4 sq. ft.) to ensure that the result meets your expectations (see Warranty). • **Do not apply to cedar wood.** • Apply only to bare material* or to material previously protected with this product.

*Sprinkle a few drops of water on the surface. If water is repelled, do not apply this product.

SURFACE PREPARATION (ESSENTIAL)

1. Protect adjacent surfaces that are not to be treated.

2. Clean the entire surface with Techniseal Wood Cleaner 60102038 (144-500), as directed on the product label.

APPLICATION

Application Conditions:

- · Surface must be clean, dry and warm to the touch.
- Temperature must be between 10°C and 25°C.
- · No rain forecast for the next 24 hours.
- Use a consistent application method over the entire surface.

Necessary Tools:

- Paintbrush
- · Masking tape, plastic tarp and other protection accessories.

This product is ready to use. Do not dilute. Shake well or stir product thoroughly before and during application.

With the paintbrush, spread evenly and saturate wood with a coat of Preservative. Avoid product accumulation. On very porous wood or on wood that will not be covered with a coating, wait 6 to 24 hours and apply a second coat. To better protect non pressure-treated wood, wait 48 hours and apply Wood Stain & Sealer (60102116, 60102117, 60102118, 60102129, 60102123, 60102124 et 60102125).

Drying: Wait 24 hours before walking on the treated surface. Prevent access during that period.

STORAGE

Store in a cool, dry place.

Store unused Preservative out of reach of children and animals.

COVERAGE

1 L cover 3 to 5 m² (30 to 50 sq. ft.). 3,78 L covers 10 to 19 m² (110 to 200 sq. ft.) Coverage will depend on surface porosity.

CLEANING & DISPOSAL

Use a mineral spirit, then a detergent and water. Do not reuse empty container; dispose of at the local recycling center. Consult your retailer or municipality regarding the disposal of empty containers or unused product.

PACKAGING

Product Code	Retail Size	Units per box	Units per pallet
60102155 (144-271)	1 L	6	480
60102156 (144-273)	3.78 L	4	180

PRECAUTION

PRECAUTION MAY IRRITATE EYES. MAY IRRITATE SKIN. Keep container closed when not in use. **KEEP OUT OF REACH OF CHILDREN.** Avoid breathing vapours. Harmful if swallowed or inhaled. Flammable: keep away from flames or sparks. Causes skin and eye irritation Potential skin sensitizer. Avoid breathing vapours, contact with skin, eyes and clothing. Wear a long-sleeved shirt, long pants, socks, shoes, and rubber gloves when applying this product. Wash with soap and water after use and before eating or smoking. Phytotoxic when wet. Toxic to fish; do not contaminate bodies of water.

WARNING

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

TRANSPORT

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

LIMITED WARRANTY

Having no control over the use of the products, Techniseal® does not guarantee finished work. Replacement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use, and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 4 sq. ft. This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty described above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods, and implied warranty of fitness of goods for any particular purpose.