



Wet Look (WLWR) High-Solid Paver Protector

Film-Forming Gloss Finish - Solvent-Based

UPDATE

January 9th, 2024

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com

U.S.A. and Canada: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- For concrete pavers
- Recommended for driveways, parking lots, patios and walkways

PROPERTIES

- Enhance the color of pavers
- Forms a protective film
- Stain guard
- Solvent-based

DESCRIPTION

Made of acrylic and plasticizers, WET LOOK (WLWR) Protector is specially designed to protect concrete pavers. With its high-solid formula, it prevents deterioration due to chemical products such as de-icing salts, while providing resistance to acids and alkalis. Its transparent film stops the penetration of contaminants, facilitating the maintenance of pavers.

DIRECTIONS

APPLICATION TO CONCRETE PAVERS

BEFORE YOU BEGIN

ALWAYS TEST on a small hidden area of approximately 4 sq. ft. to ensure that result meets your expectations (see Warranty).

- **Do not apply** to natural stone, wet-cast, stamped or poured concrete. • Do not apply to polished material. • Apply only to bare material* or to material previously sealed with WL5 or WLWR Protectors from Techniseal[®]. • Wait until the Protector is worn before recoating the surface (2 years minimum). • With the appropriate stripper, remove any unknown coating that was previously applied. • Wear adequate protective clothing and an OSHA approved respirator for acetone.

***ABSORPTION TEST:** Sprinkle a few drops of water on surface. If water is absorbed, move on to the next point. If water is repelled, do not apply this product.

SURFACE PREPARATION (CONCRETE PAVERS)

1. Protect vegetation, vehicles and adjacent surfaces that are not to be treated.
2. Remove stains with the appropriate Techniseal stain removers.
3. Prepare the entire surface with Techniseal Paver Prep (efflorescence cleaner), as directed on product label.

APPLICATION CONDITIONS

- Surface must be clean, dry and warm to the touch.
- Temperature must be between 50 °F and 85 °F during the application and for the next 24 hours.
- No rain should be forecasted for the next 24 hours.
- Sprinkler system must be turned off.
- Use a consistent application method over the entire surface.

NECESSARY TOOLS

- Low-pressure solvent resistant (acetone) airless sprayer (< 50 psi) or solvent resistant (acetone) pump sprayer (best practice)
- Techniseal Slit-Foam Roller and solvent-resistant paint tray.

Do not dilute. Shake well or stir product before and during application. If project requires more than one container, blend all containers together to ensure uniformity. Work in sections of no more than 50 sq. ft.

Sprayer Application (Best Practice): Saturate a section with a single coat of Protector. With the roller, remove the excess on the surface before it dries. Repeat for subsequent sections, maintaining a wet edge in order to avoid overlapping marks.

Roller Application: Saturate the surface with a single coat of Protector, avoiding an accumulation of excess product. Maintain a wet edge in order to avoid overlapping marks.

TRAFFIC

Pedestrian: 24 h. / Vehicular: 48 h to 72 h. Block access during that period.

CAUTION

• Any new concrete product has the potential to produce efflorescence (whitish salts) on its surface. This Protector, like any film-forming coating, carries a small risk of trapping efflorescence beneath its film. Consult the paver manufacturer or contact Techniseal® at 1 800 465-7325 for more information. • Do not attempt sprayer application on windy days. • Do not apply this product over a blotchy or hazed surface. • Inadequate surface cleaning can result in uneven finish. • This product will make the surface more slippery when wet. If slipping is a concern, consider adding Surefoot anti-slip grit from Techniseal® in the Protector before the application or using Color Boost (CB) Protector. Color Boost (CB) is not a joint stabilizer. • Wait 30 days after the installation of polymeric sand before sealing the pavers. • An over-accumulation of product could lead to surface whitening. • Extreme climate or heavy traffic could limit product longevity.

COVERAGE

Single-coat application: 1 gallon covers up to 150 sq. ft. per coat / 5 gallons cover up to 750 sq. ft. per coat.

Coverage will depend on joint width and type as well as surface porosity.

STORAGE

Store in a cool, dry place.

CLEANING & DISPOSAL

Wash tools with lacquer thinner. Consult your retailer or municipality regarding the disposal of empty containers or unused product.

PACKAGING

Product	Product code	Size	Units per box	Units per pallet
Wet Look (WLWR) Protector	60301302	1 gallon	4	180
	60301303	5 gallons	-	48

WARNING

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

TRANSPORT

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

LIMITED WARRANTY

Having no control over the use of the products, Techniseal® does not guarantee finished work. Replacement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use, and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 4 sq. ft. This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty described above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods, and implied warranty of fitness of goods for any particular purpose.