



Carbopoxy+ Garage Floor Finishing Coat Super-Glossy Finish

UPDATE

May 14th, 2022

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com
U.S.A. and Canada: dial 1 800 465-7325
Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Recommended for garage floor

PROPERTIES

- Offers optimal protection to the Carbopoxy[®] System
- Provides resistance to hot tire pick-up

DESCRIPTION

Techniseal[®] Carbopoxy[®]+ Garage Floor Finishing Coat is a water-based single-component clear Protector made from acrylic and epoxy-modified polycarbonate. Carbopoxy[®]+ does not require the mixing of two components and is thus ready to apply. Microporous, it allows concrete to breathe. Once applied over coloured Carbopoxy[®] as a finishing coat, it provides a super-glossy finish as well optimal protection. Easy to clean, Carbopoxy[®]+ reduces dust and prevents crumbling of the surface.

DIRECTIONS

BEFORE YOU BEGIN

- **Wait 30 days** before applying to new concrete. • Apply only to concrete previously sealed with this product or with the coloured Carbopoxy[®]. • **ALWAYS TEST** on a small hidden area of approximately 0.4 m² (4 sq. ft.) to ensure that result meets your expectations.

IMPORTANT: Carry out a **MOISTURE TEST** by applying a piece of polythene of approximately 40 cm X 40 cm (16" X 16") to the floor and securing it with heavy duty adhesive tape. Wait 24 hours and verify if water drops are present under the piece of polythene. If so, this signifies that moisture is present in the concrete: **DO NOT APPLY PRODUCT** and call Techniseal[®] at 1 800 465-7325. If the piece of polythene is dry, you may proceed with the application of the Carbopoxy system.

SURFACE PREPARATION (ESSENTIAL)

No preparation required if applied less than 48 hours following the application of the coloured Carbopoxy[®] or the Carboprime 60102115 (149-763).

APPLICATION

Application Conditions:

- Surface must be clean, warm to the touch and dry (24 to 48 hours without dampness).
- DO NOT apply if temperature inside garage is below 15 °C when applying the product and during the 24-hour drying period.

- Use a consistent application method over entire surface.

Required Tools: Pile roller for semi-smooth surfaces (7 to 10 mm).

Do not dilute. Shake well or stir product before and during application.

Using a pile roller for semi-smooth surfaces, apply a single coat of Protector. Maintain a wet edge in order to prevent overlap marks. To obtain maximum protection and a more glossy finish, let dry 24 hours and apply a second coat following the same method.

Traffic: Pedestrian: 24 hours / Vehicular: Wait 15 days before parking a car on the treated surface. If this is not possible, protect surfaces that are in contact with car tires with pieces of cardboard.

STORAGE

Keep from freezing. Store in a cool, dry place.

CLEANING & DISPOSAL

Wash tools and hands with warm soapy water. Consult your retailer or municipality regarding the disposal of empty containers or unused product.

CAUTION

- Do not apply to a surface that is dirty or dusty.
- There should be no water on the surface within 30 days following application.
- On average quality or crumbled concrete, the product may wear out prematurely in areas where cars come and go.
- If needed, simply touch up those areas.
- During colder periods, the product may not adhere properly to surfaces located near a door.

COVERAGE

When applied over coloured Carbopoxy®: 3.78 L cover up to 45 m² (500 sq. ft.). When applied over bare concrete: 3.78 L cover up to 25 m² (275 sq. ft.). Coverage will depend on surface porosity. The second coat will require considerably less product.

PACKAGING

Product code	Colour	Retail Size	Units per box	Units per pallet
60102126 (149-303)	Clear	3.78 L	2	180

WARNING

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

TRANSPORT

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

LIMITED WARRANTY

Techniseal® warranties CARBOPOXY+® against manufacturing defects. As Techniseal® has no control over surface preparation and product application, results cannot be guaranteed. The Techniseal® warranty is limited only to the replacement of a product proven to be defective, and will never cover the cost of labour. A proof of purchase will be required for any claim. Notice : User should make sure that this product meets their needs by carrying out a test under anticipated conditions of use on a 0.4 m² (4 sq.ft.) area. In the event that no test was carried out, the warranty will only apply to 0.4 m² (4 sq.ft.).