



RoofKeeper™ Elastomeric Shingle Coating 10 Year warranty

UPDATE

February 8, 2024

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site:
techniseal.com

Canada and U.S.A.: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Any surface covered with asphalt shingles: houses, mobile homes, cottages and sheds
- Sheet metal roofing
- Sloped or vertical surfaces

PROPERTIES

- Locks granules in place; extends the life of shingles
- Ideal for areas exposed to strong winds (up to 150 km/h)
- Allows for a change of roofing colour

DESCRIPTION

Made of 100% acrylic elastomeric resin, RoofKeeper™ Elastomeric Shingle Coating extends the life while improving the original appearance of your roofing. It modifies or rejuvenates the colour of the roof following partial repairs. Ultra-adherent, it forms a protective coat against the elements and the harsh Canadian climate; it prevents deterioration caused by frost, rain, UV rays and the disbondment of granules. Water-based and free of bitumen, RoofKeeper™ does not release unpleasant fumes, and it is environmentally-friendly.

DIRECTIONS

BEFORE YOU BEGIN

- Do not apply to a flat roof or to roofing covered with tar, gravel or a rubber membrane.
- If the roof is leaking, make the appropriate repairs.
- Do not apply to roofing that is deteriorated in such a way that it needs to be replaced.
- Access to roof safely. Use appropriate safety measures during work.
- Wear adequate protective clothing and goggles.
- **ALWAYS TEST** product on a small hidden area of approximately 0.4 m² (4 sq. ft.) to ensure that result meets your expectations (see Warranty).

INSTALLATION ON ASPHALT SHINGLES

SURFACE PREPARATION (ESSENTIAL)

1. Cover vegetation, vehicles and adjacent surfaces that are not to be treated.
2. Remove lichens, mildew or fungus with an appropriate roof cleaner..
3. Replace missing or damaged shingles.
4. Seal off cracks with appropriate Techniseal® repairing products.
5. Around vents, chimneys, flues and repaired areas, replace tar with Techniseal® Weatherproof Sealant 70978066 (140-701).
6. Apply RoofKeeper™ under curled or buckled shingles, then lock them in place with appropriate staples.
7. Remove any debris and detached granules with a leaf blower. Avoid using a push broom as granules could be detached.

INSTALLATION ON METAL ROOF

SURFACE PREPARATION (ESSENTIAL)

1. Protect vegetation, vehicles and adjacent surfaces that are not to be treated.
2. Remove lichens, mildew or fungus with an appropriate roof cleaner.
3. Remove loose rust and paint residue with a steel brush or a pressure washer.
4. Replace heavily damaged sheet-metal sections.
5. Replace tar with Techniseal® Weatherproof Sealant 70978066 (140-701) around vents, chimneys, flues and repaired areas.
6. Punch badly hammered nail heads.
7. Prime cracks, nail heads and repaired sections with Techniseal® Weatherproof Sealant 70978066 (140-701).
8. Remove debris with a leaf blower.

APPLICATION

Application Conditions:

- Roofing must be clean, dry and warm to the touch.
- Preferably apply early in the morning; temperature must be between 10°C and 25°C.
- No rain forecasted for the next 24 hours.
- Use a consistent application method over entire surface.

Required tools:

- Trimming paintbrush
- Techniseal® Thick-Pile Roller (31 mm) 70978075 (145-940)
- Airless sprayer for high-viscosity paints (optional)

Do not dilute. Shake well or stir product before and during application. Intermix cans of the same product to ensure colour uniformity.

Trim using a paintbrush. Applying product vertically (north to south), saturate the surface with a first coat of coating using the thick-pile roller. Let dry for 18 to 24 hours.

Apply a second coat, proceeding by horizontal strips (east to west). Cover 5 to 6 shingle rows at a time, over all roof width. Repeat for subsequent sections, maintaining a wet edge in order to prevent overlap marks.

CAUTION

- This product is not intended to seal leaks or to waterproof roofing.
- Do not apply to a roof that does not have proper ventilation or insulation.
- Application to excessively hot roofing will make coating dry too quickly, which will leave overlap marks.
- This product will make the surface more slippery when wet.
- An over-accumulation of product could reduce the coating's microporosity.

COVERAGE

Coverage will vary according to roof condition. Old shingles will generally absorb more product. Two coats of product must be applied in order to benefit from the warranty. The cumulative quantity of the two coats must be 1 liter of product per 1.9 m² (20 ft²). The second coat will cover more surface area than the first.

STORAGE

Keep from freezing. Store in a cool, dry place.

CLEANING & DISPOSAL

Wash tools and hands with warm soapy water. Consult your retailer or municipality regarding the disposal of empty containers or unused product.

PACKAGING

Colour	Product code	Retail Size	Units per pallet
Black	60102181 (140-407)	15 L	60
Brown	60102174 (140-427)	15 L	60
Grey	60102178 (140-447)	15 L	60

WARNING

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

TRANSPORT

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

LIMITED 5-YEAR WARRANTY

Techniseal® warrants RoofKeeper™ treatment against manufacturing defects. This warranty will be void if product becomes defective due to freezing. During the first year following purchase, Techniseal® will replace the product if it fails to perform within specifications. After this first year, the quantity replaced will drop by 10% (10-year warranty) or by 20% (5-year warranty) for each subsequent year. This warranty is limited to the replacement of the product and does not cover labour costs. This warranty will be void if: product was applied on a defective roof; an insufficient amount of product was applied (see coverage information on label); application was not performed according to directions on the label. User should make sure that product meets his or her needs by carrying out a test on a 0.4 m² (4 sq. ft.) surface, under anticipated conditions of use. In the event that no test was carried out, the warranty will only apply to 0.4 m² (4 sq. ft.). A proof of purchase will be required for any claim. This limited warranty excludes any liability for any consequential, incidental, indirect or special damages.