



## BORDERBOND™

### Fortifier for Border Pavers

#### UPDATE

**December 22, 2022**

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: [techniseal.com](http://techniseal.com)

U.S.A. and Canada: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

#### APPLICATIONS

- Residential driveways, sidewalks, pool decks, patios, courtyards, garage floors
- Commercial and light industrial driveways, sidewalks, walkways, courtyards

#### PROPERTIES

- Easy to use – Straight from the bottle
- Easily mixes with DriBond
- Maximizes bond strength of DriBond

#### DESCRIPTION

BorderBond is a ready-to-use liquid fortifier that mixes with DriBond to bond border pavers firmly to the concrete base.

#### DIRECTIONS

##### BEFORE YOU BEGIN

Before proceeding with the installation, make sure you have an up-to-date technical data sheet in hand and visit [techniseal.com](http://techniseal.com) to watch the application video. **ALWAYS TEST** on a small hidden area of approximately 4 sq. ft. to ensure that result meets your expectations (see Warranty).

##### Necessary tools:

- Shovel or garden hoe
- Mixing whip and drill (optional)
- Wheelbarrow or any suitable mixing container
- 1/2" x 1/2" square notch trowel or margin trowel

##### PREPARATION

Shake container well before use. Do not dilute. Mix one bag of DriBond with one container of BorderBond. To obtain a more uniform consistency, it is recommended to mix both products gradually, in two or more doses. Mix must have a smooth, creamy consistency.

## APPLICATION

1. Remove any dry DriBond from the border areas. Surface must be clean and dry.
2. Using a 1/2" x 1/2" square notch trowel or a margin trowel, apply mix to the borders and transitions as necessary. This will create a mortar bed on which to lay the pavers.
3. Install border pavers as described on the DriBond bag or technical data sheet.
4. Remove any excess product from the edge of the finished paved area. There should be **no air pockets or voids** under the border pavers. **Never** allow the border pavers to protrude past the edge of the existing concrete.

**Note:** Although not mandatory, wetting the concrete surface prior to applying the BorderBond mix will insure optimal bond strength and adhesion.

## CLEANING

Clean tools and hands with warm water.

## COVERAGE

1.58 gal of BorderBond mixed with one bag of DriBond cover approximately 30 linear feet, based on a 12" wide border. Coverage will depend on surface condition and desired BorderBond bedding thickness.

Approximate Coverage Chart for a 1.58 gal of BorderBond:

Border Width	Coverage in linear feet
4"	90 to 120
6"	60 to 70
9"	40 to 45
12"	30 to 35

## STORAGE

2 years when kept in an unopened container and stored in a cool and dry place, away from the sunlight and with adequate ventilation. For an opened container, shelf life is approximately 2 hours.

## PACKAGING

BorderBond	Product Code	Color	Retail Size	Units per Box	Boxes per Pallet
	60050792 (221-B05)	N/A	1.58 gal.	2	36

## WARNING

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit [www.techniseal.com](http://www.techniseal.com) or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

**KEEP OUT OF REACH OF CHILDREN**

## TRANSPORT

---

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit [www.techniseal.com](http://www.techniseal.com) or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

## LIMITED WARRANTY

---

Manufacturer, having no control over the use of the materials, does not guarantee finished work. Replacement of any defective product shall be the buyers sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 4 sq.ft. This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty made above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods and implied warranty of fitness of goods for any particular purpose.