



Crack Filler for Concrete

UPDATE

December 13, 2022

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: techniseal.com

Canada and U.S.A.: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Floors, walls, sidewalks, steps, pool decks, roughcast, mortar, etc.

PROPERTIES

- Ideal for floors, walls, sidewalks, steps, roughcast, mortar, etc.
- Fills cracks 0.5 to 1 cm wide
- Granular texture
- Dries quickly, very durable

DESCRIPTION

Flexible and very durable, Techniseal[®] Crack Filler for Concrete is an acrylic compound specially designed to repair concrete floors, mortar joints, sidewalks, steps, pool decks, roughcast and any other concrete or masonry surface. Its texture and colour perfectly blend with surfaces. Since it is paintable, it is ideal for repairs done prior to the application of a coating. Easy to apply, Techniseal[®] Crack Filler for Concrete dries quickly, strongly adheres to inner walls of cracks and perfectly resists the elements. Water-based and containing very little solvent (V.O.C.: 43.43 g/L), it is environmentally friendly and free of unpleasant fumes.

Note: This product is formulated for cracks 1 cm (1/2") wide or less.

DIRECTIONS

Surface should be clean and dry. Temperature should be above 5°C. Applying steady pressure, fill cracks to surface level; smooth if desired. Let dry completely (for at least 24 hours) before applying a coating or driving on the surface. Cleaning of tools: Wash with water before product dries.

Note: Do not apply if rain or frost is forecasted within 12 hours. Store at a temperature above 15°C.

PACKAGING

Product code	Retail Size	Units per box	Units per pallet
70978057 (149-781)	304 ml	12	1296

WARNING

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

TRANSPORT

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

LIMITED WARRANTY

Techniseal® warrants this Protector against manufacturing defects. As Techniseal® has no control over surface preparation and product application, results cannot be guaranteed. The Techniseal® warranty is limited only to the replacement of a product proven to be defective, and will never cover the cost of labour. A proof of purchase will be required for any claim. Notice : User should make sure that this product meets their needs by carrying out a test under anticipated conditions of use on a 4 sq.ft. (0.4 m²) area. In the event that no test was carried out, the warranty will only apply to 4 sq.ft. (0.4 m²).