



Hardscape Cleaner for Pavers

UPDATE

December 7, 2022

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com

Canada and U.S.A.: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Pavers, slabs and retaining walls made of concrete or natural stone and wet-cast.
- Driveways, patios, terraces, commercial parking lots, pedestrian areas, etc.

PROPERTIES

- Dislodges ground-in dirt and brightens up colours
- For routine maintenance

DESCRIPTION

Techniseal® Hardscape Cleaner is formulated to remove ground-in dirt from the surface of most hardscape materials such as concrete pavers, slabs and walls, natural stone¹ and wet-cast pavers². Hardscape Cleaner works without damaging or discolouring the material. It brightens up the colour and cleans evenly. It is ideal for routine maintenance.

¹Not intended for use on marble, limestone or any other natural stone not resistant to acid. Do not apply on polished or glazed stones.

²Given the great variability in porosity and composition of wet-cast pavers, Techniseal can not guarantee the result obtained. A test on a small area is recommended before doing the cleaning of the entire surface.

DIRECTIONS

BEFORE YOU BEGIN

• Wear adequate protective clothing. • To ensure the results will meet your expectations, **ALWAYS TEST** the product on a small hidden area of approximately 0.4 m² (4 sq. ft.). • **DO NOT** use on poured or stamped concrete. • **DO NOT** apply under blazing sun. • **DO NOT** apply with a mop or a broom. • **NEVER** let Hardscape Cleaner dry on the surface; keep it wet until it is completely rinsed off. • **NEVER** apply the product at full strength; dilute with water. • Application of a Protector: Clean the surface with Techniseal® Pre-Seal Cleaner (141-534) as directed on label.

PREPARATION

Wetting: To reduce the penetration of Hardscape Cleaner into sand joints and thus make product easier to rinse, first wet the surface to saturate joints with water; then let the surface dry, and apply product.

Dilution: For easy application, attach a Techniseal® Exact sprayer (145-900) to the container and connect a garden hose to it. Adjust the sprayer to the A mode. Always test the dilution on a small area first. If a sprayer is not available, in a plastic watering can, dilute 1 part product in 9 parts water. Always pour product in water.

APPLICATION

Work one section of 18 m² (200 sq. ft.) at a time. Using the watering can or the sprayer, pour or spray the diluted solution, making sure to cover the whole surface of the section without leaving any dry spots. Gently scrub using a push broom, and **rinse immediately and thoroughly** until all traces of foam disappear. Repeat cleaning on the next section, overlapping the edges of previously cleaned sections. Once the entire surface is clean, rinse thoroughly and let dry. Repeat if necessary.

COVERAGE

4 litres of concentrated product clean up to 74 m² (800 sq. ft.). Coverage will depend on surface condition and dilution.

STORAGE

Store in cool and dry place with adequate ventilation.

PACKAGING

Product code	Retail Size	Units per box	Units per pallet
60101011 (141-503)	4 L	4	144

WARNING

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

TRANSPORT

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

LIMITED WARRANTY

Techniseal® warrants this Cleaner against manufacturing defects. As Techniseal® has no control over surface preparation and product application, results cannot be guaranteed. The Techniseal® warranty is limited only to the replacement of a product proven to be defective, and will never cover the cost of labour. A proof of purchase will be required for any claim. Notice : User should make sure that this product meets their needs by carrying out a test under anticipated conditions of use on a 0.4 m² (4 sq.ft.) area. In the event that no test was carried out, the warranty will only apply to 0.4 m² (4 sq.ft.).