



Instant Leak Sealer

UPDATE

January 10th, 2023

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com

Canada and U.S.A.: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Adheres to most material: shingles, sheet metal, aluminium, copper, glass, wood and PVC

PROPERTIES

- Works on gutters, roofs, concrete, heating ducts, PVC, etc.
- Stays flexible and waterproof
- Will not crack or peel
- Seals out rust and corrosion
- Covers up to 1.8 m² (20 sq.ft.)

DESCRIPTION

Techniseal[®] Instant Leak Sealer is a unique spray product that easily and quickly seals cracks. It leaves an abrasion resistant coating that stays flexible, will not crack and is impervious to water. It seals out rust and corrosion. Product can be painted on.

DIRECTIONS

Shake well. Do not apply below 5°C or above 30°C. Apply only to a clean and dry surface. Spray surface with short, even strokes from a distance of 25 to 30 cm (10 to 12"). Multiple coats may be applied. Allow 20 to 30 minutes between coats. For a more uniform finish, use a 2.5 cm (1") paintbrush to spread the product evenly.

Heating ducts: Wait until ducts have cooled down before spraying sealer.

COVERAGE

Covers up to 1.8 m² (20 sq.ft.).

PACKAGING

Colour	Product code	Retail Size	Units per box
Clear	70978078 (140-801)	369 g spray can	12
Black	70978079 (140-811)	369 g spray can	12
White	70978077 (140-821)	369 g spray can	12
Aluminium	70978076 (140-831)	369 g spray can	12

WARNING

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

TRANSPORT

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

LIMITED WARRANTY

Manufacturer's liability is limited to the replacement of the product. A proof of purchase will be required for any claim.