



# NuLook

## Tinted Protector for Concrete Pavers

### Semi-Gloss finish

#### UPDATE

---

**December 12, 2022**

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: [techniseal.com](http://techniseal.com)

U.S.A. and Canada: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

#### APPLICATIONS

---

- Pavers and other concrete surfaces

#### PROPERTIES

---

- Semi-transparent
- Ideal for driveways, parking lots, walkways and patios
- Covers up to 14 m<sup>2</sup> (150 sq. ft.)
- Water based

#### DESCRIPTION

---

Made of acrylic and urethane, NuLook<sup>®</sup> Tinted Protector is specially designed to protect concrete pavers. Semi-transparent, it modifies or rejuvenates the original colour of pavers. It prevents deterioration due to chemical products such as de-icing salts, while providing resistance to acids and alkalis. Its surface film forms an invisible bond that stops the penetration of contaminants, facilitating the maintenance of pavers. Water-based, NuLook<sup>®</sup> Tinted Protector does not release unpleasant fumes, and it is environmentally-friendly.

#### DIRECTIONS

---

##### BEFORE YOU BEGIN

- Do not apply to natural stone or to wet-cast pavers or stamped concrete.
- Application to poured concrete: Contact Techniseal<sup>®</sup> for more information at 1 800 465-7325.
- Apply only to bare material\*, or to material previously sealed with this product or with Techniseal<sup>®</sup> Natural Look EV Protector (141-304).
- Wait until the Protector is worn before recoating the surface (minimum 2 years).
- With the appropriate Techniseal<sup>®</sup> stripper, remove any unknown coating that was previously applied.
- **ALWAYS TEST** on a small hidden area of approximately 0.4 m<sup>2</sup> (4 sq. ft.) to ensure that result meets your expectations (see Warranty).

\*ABSORPTION TEST: Sprinkle a few drops of water on surface. If water is absorbed, move on to the next point. If water is repelled, do not apply this product.

## SURFACE PREPARATION (ESSENTIAL)

1. Cover vegetation, vehicles and adjacent surfaces that are not to be treated.
2. Remove stains with the appropriate Techniseal® stain removers.
3. Prepare the entire surface with Techniseal® Pre-Seal Cleaner (141-534), as directed on product label.

## APPLICATION

### Application Conditions:

- Surface must be clean, dry and warm to the touch.
- Temperature must be between 10°C and 30°C.
- No rain should be forecasted for the next 24 hours.
- Sprinkler system must be turned off.
- Use a consistent application method over the entire surface.

### Necessary Tools:

- Low-pressure airless sprayer (< 50 psi) or pump sprayer
- 10 to 12 mm polyester nap roller and paint tray

Do not dilute. Shake well or stir product before and during application. Intermix cans of the same product to ensure colour uniformity. Do not trim; use a cardboard for edges.

Work in sections of no more than 4.6 m<sup>2</sup> (50 sq. ft.). Using the sprayer, **saturate** the surface with a coat of Protector. With the roller, remove excess on the surface before it dries. Repeat for subsequent sections, maintaining a wet edge in order to prevent overlap marks.

For a darker colour and a higher gloss, apply a second coat. Wait until the first coat is dry (+/- 4 hours), then apply a second coat following the same method.

**Traffic:** Pedestrian: 24 h. / Vehicular: 48 to 72 h. Block access during that period

## STORAGE

Keep from freezing. Store in a cool, dry place.

## CLEANING & DISPOSAL

Wash tools and hands with warm soapy water. Consult your retailer or municipality regarding the disposal of empty containers or unused product.

## CAUTION

• Any new concrete product has the potential to produce efflorescence (whitish salts) on its surface. This Protector, like any film-forming coating, carries a small risk of trapping efflorescence beneath its film. Consult the paver manufacturer or visit [techniseal.com](http://techniseal.com) for more information. • Do not attempt sprayer application on windy days. • Do not apply this product over a blotchy or hazed surface. • Trimming with a brush or a roller could leave marks. • This product will make the surface more slippery when wet. • An overaccumulation of product could lead to surface whitening. • Extreme climate or heavy traffic could limit product longevity.

## COVERAGE

3.78 L cover up to 14 m<sup>2</sup> (150 sq. ft.).

## PACKAGING

Product Code	Color	Pro Size	Units per box	Units per pallet
60102152 (141-343)	Charcoal	3.78 L	2	180

## WARNING

---

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit [www.techniseal.com](http://www.techniseal.com) or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

### KEEP OUT OF REACH OF CHILDREN

## TRANSPORT

---

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit [www.techniseal.com](http://www.techniseal.com) or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

## LIMITED WARRANTY

---

Having no control over the use of the products, Techniseal® does not guarantee finished work. Replacement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use, and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 0.4 m<sup>2</sup> - 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 0.4 m<sup>2</sup> (4 sq. ft.). This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty described above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods, and implied warranty of fitness of goods for any particular purpose.