



Paint, Tar and Rubber Remover for Pavers

UPDATE

January 13th, 2023

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: techniseal.com
Canada and U.S.A.: dial 1 800 465-7325
Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Concrete pavers and slabs and natural stone.
- Driveways, patios, terraces, commercial parking lots, pedestrian areas, etc.

PROPERTIES

- Removes paint, tar, rubber and chewing gum stains.
- Water-Rinsable

DESCRIPTION

Techniseal[®] Paint, Tar and Rubber Remover for pavers effectively dissolves paint, tar or bitumen, rubber and chewing gum on pavers, slabs, concrete and masonry.

DIRECTIONS

BEFORE YOU BEGIN

- Wear adequate protective clothing. • **ALWAYS TEST** on a small hidden area to ensure that result meets your expectations.
- Surface should, ideally, be warm to the touch.

APPLICATION

Cover stain generously with Remover and let work for 5 to 10 minutes. Reapply product and, using a small nylon scrub brush such as the Techniseal Stain remover brush (145-910), scrub until stain is dissolved. **DO NOT** let dry; rinse immediately.

NOTE: This product dissolves any sealant; apply a new coat of sealant on stripped surface.

PACKAGING

Product code	Size	Units per box	Units per pallet
60100111 (141-541)	1 L	6	480

WARNING

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

ATTENTION / CAUTION IRRITANT

MAY IRRITATE EYES. MAY IRRITATE SKIN.

Do not get in eyes. Do not get on skin or clothing.

Keep away from flames or sparks. **KEEP OUT OF REACH OF CHILDREN.**

FIRST AID TREATMENT

Contains: Solvent naphtha (petroleum), light arom.; dimethyl glutarate; N-methyl-2-pyrrolidone; dimethyl adipate; Solvent naphtha (petroleum), heavy arom.; 1,2,4-trimethylbenzene and Poly(oxy-1,2-ethanediyl), α -[(1,1,3,3-tetramethylbutyl)phenyl]- ω hydroxy-

If swallowed, call a Poison Control Centre or doctor immediately. DO NOT induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water.

EMERGENCY PHONE: CANUTEC (613) 996-6666

SEE SAFETY DATA SHEET FOR THIS PRODUCT

TRANSPORT

Land : Exemption TMD class 3, GE : III

Sea : Can be transported in limited quantities

LIMITED WARRANTY

Having no control over the use of the products, Techniseal® does not guarantee finished work. Re-placement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suit-ability of the product for it intended use, and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 0,4 m²-4 sq. ft.). This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty described above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty or merchantability or goods, and im-plied warranty of fitness of goods for any particular purpose.