



RG+ Concrete Adhesive

UPDATE

March 23, 2023

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: techniseal.com
U.S.A. and Canada: dial 1 800 465-7325
Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- For pavers, slabs and retaining walls
- Any concrete or masonry surface

PROPERTIES

- Remains flexible
- Premium advanced formula
- Elastomeric-resin-based compound
- Ideal for the construction of retaining walls
- Can also be used on wet or frozen surfaces

DESCRIPTION

Techniseal[®] RG+ Concrete adhesive is an elastomeric resin based compound that is specially formulated for the construction of concrete hardscapes. Remaining flexible, it is ideal for the construction of retaining walls. Most effective on dry surfaces, it can also be used on wet or frozen surfaces. It provides a strong bond and resists the elements (water, frost, etc.).

The RG+ Adhesive meets or exceeds the following standards: ASTM D3498, APA AFG-01, ASTM C557

DIRECTIONS

Surface should be clean and, ideally, dry. Apply a maximum thickness of 3/8"; join pieces together immediately with a slight twisting motion. If surface is wet or frozen, curing will take longer.

Cleaning of tools: Use mineral spirits.

COVERAGE

- A 10 oz tube, a 3/8 in. bead covers up to 15 ft.
- A 28 oz tube, a 3/8 in. bead covers up to 41 ft.

STORAGE

Product must be kept in its original, unopened and tightly sealed container, and stored in a dry and well ventilated place with controlled temperature (40 °F to 75 °F). Keep sheltered from weather and direct sunlight. In proper storage conditions, the product's shelf life is 2 years following production (see date on packaging).

PACKAGING

Name	Product Code	Retail Size	Units per box	Units per pallet
RG+	60050381 (221-791)	10 fl. oz.	12	1,296
	60050541 (221-792)	28 fl. oz.	12	456

WARNING

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product’s Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

TRANSPORT

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product’s Safety Data Sheet (SDS).

LIMITED WARRANTY

Having no control over the use of the products, Techniseal® does not guarantee finished work. Replacement of any defective product shall be the buyer’s sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use, and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area under projected conditions of use.