



Rust Remover for Pavers

UPDATE

December 20, 2022

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com Canada and U.S.A.: dial 1 800 465-7325 Others: dial (514) 523-8324 (Canada)

APPLICATIONS

Concrete pavers, slabs and walls

PROPERTIES

- · Effectively removes stains caused by steel, rusted metal objects, fertilizers, etc.
- · Contains no muriatic acid

DESCRIPTION

Techniseal[®] Rust Remover for pavers takes out rust from pavers made of concrete. It effectively dissolves stains caused by dripping rusted water, steel streaks, fertilizer granules¹, etc. Since it contains no muriatic acid, it won't damage the material. For bare or previously sealed surfaces.

¹To remove fertilizer stains from a large surface, it is recommended to use Techniseal[®] Pre-Seal Cleaner (141-534).

DIRECTIONS

BEFORE YOU BEGIN

• Wear rubber gloves and safety goggles. • ALWAYS TEST on a small hidden area to ensure that result meets your expectations.

APPLICATION

Wet the stain and cover it with Rust Remover; using a a small nylon scrub brush such as the Techniseal Stain remover brush (145-910), scrub the stain until dissolved; rinse immediately with water. If rust persists, repeat the operation. **IMPORTANT :** Pavers may appear spotted after the use of Rust Remover. This is called a "clean stain". For uniform results, clean the entire surface with Techniseal[®] Pre-Seal Cleaner (141-534). Rust streaks left by metal snowploughs may be difficult to remove. **Do not use on non-acid resistant natural stone, wet-cast pavers or poured concrete.**

STORAGE

Product must be kept in its original, unopened and tightly sealed container, and stored in a dry and well ventilated place with controlled temperature 4 °C to 24 °C (40 °F to 75 °F). Keep sheltered from weather and direct sunlight.

PACKAGING

Product code	Size	Units per box	Units per pallet
60100115 (141-521)	1 L	6	480

WARNING

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

TRANSPORT

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

LIMITED WARRANTY

Techniseal[®] warranties this Remover against manufacturing defects. As Techniseal[®] has no control over surface preparation and product application, results cannot be guaranteed. The Techniseal[®] warranty is limited only to the replacement of a product proven to be defective, and will never cover the cost of labour. A proof of purchase will be required for any claim.