



RUST REMOVER for PAVERS

UPDATE

January13th, 2023

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com U.S.A. and Canada: dial 1 800 465-7325 Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Sealed or bare surfaces
- Pavers and slabs made of concrete
- Driveways, pool decks, patios, terraces, commercial parking lots, pedestrian areas, etc.

PROPERTIES

- Effectively removes stains caused by steel, rusted metal objects, fertilizers, etc.
- For bare or previously sealed surfaces
- · Contains no muriatic acid

DESCRIPTION

Techniseal[®] Rust Remover for Pavers takes out rust from concrete pavers. It effectively dissolves stains caused by dripping rusted water, steel streaks, fertilizer granules¹, etc. Since it contains no muriatic acid, it won't damage the material. Ideal for bare or previously sealed surfaces.

¹To remove fertilizer stains from a large surface, it is recommended to use Techniseal[®] Paver Prep.

DIRECTIONS

BEFORE YOU BEGIN

• ALWAYS TEST on a small hidden stain to ensure that result meets your expectations. • Do not use on natural stone that is not acid-resistant, wet-cast pavers, poured or stamped concrete. • Wear rubber gloves and safety goggles.

APPLICATION

Wet the stain and cover it generously with Rust Remover. Using a nylon scrub brush, scrub the stain until it is dissolved; rinse immediately with water. If rust persists, repeat the operation.

IMPORTANT: Pavers with efflorescence may appear spotted after the use of Rust Remover. For a uniform result, clean the entire surface with Paver Prep from Techniseal[®]. Rust streaks left by metal snowploughs may be difficult to remove.

STORAGE

Product must be kept in its original, unopened and tightly sealed container, and stored in a dry and well ventilated place with controlled temperature (40 °F to 75 °F). Keep sheltered from weather and direct sunlight.

PACKAGING

Product Code	Retail Size	Units per box	Units per pallet
60101956 (121-521)	1 qt.	6	480

WARNING

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

TRANSPORT

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

LIMITED WARRANTY

Techniseal[®] warrants this product against manufacturing defects. As Techniseal[®] has no con-trol over surface preparation and product application, results cannot be guaranteed. The Tech-niseal[®] warranty is limited only to the replacement of a product proven to be defective and will never cover the cost of labor. A proof of purchase will be required for any claim.