



## SLURRY REMOVER FOR PAVERS AND SLABS

### UPDATE

---

**December 7, 2022**

Make sure that you have an up-to-date technical data sheet in hand by consulting our website:

[techniseal.com](http://techniseal.com)

U.S.A. and Canada: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

### APPLICATIONS

---

- Bare surfaces
- Concrete or clay pavers and slabs

### PROPERTIES

---

- Removes cement slurry and polymeric sand haze

### DESCRIPTION

---

TECHNISEAL® SR SLURRY REMOVER FOR PAVERS AND SLABS is the most effective product available for removing cement slurry and polymeric sand haze on concrete or clay pavers and slabs.

### DIRECTIONS

---

Read the Material Safety Data Sheet before using this product. **Wear acid-resistant clothing, boots, gloves and safety goggles.**

#### DILUTION:

**Principle: To use the strongest concentration of product without etching or discoloring pavers. A weaker concentration will increase the labor factor.**

1. Into a plastic watering can, dilute 1 part product in 8 or more parts water.
  2. Test the concentration on spare pavers or on a small hidden area of approximately 4 sq. ft. Test area or spare pavers must be wet.
- If the product etches or discolors the pavers: lower the concentration (1 part product in 10 parts water) until the product no longer etches or discolors the pavers.
  - If the product DOES NOT etch or discolor the pavers: to increase product efficiency and reduce scrubbing, you may use a stronger concentration. The concentration must be strong enough to remove slurry without etching or discoloring pavers.

#### IMPORTANT:

**Always test diluted product before using on the entire surface.**

**ALWAYS POUR THE SLURRY REMOVER INTO WATER; NEVER POUR WATER INTO THE PRODUCT.**

**WETTING:**

To prevent product penetration and make rinsing easier, first saturate surface with water. Always work on a wet surface.

**APPLICATION:**

**Do not use on flagstone or on natural stone.**

Cement slurry on concrete pavers or slabs:

1. If application is done on pavers with new polymeric sand joints, **wait 30 days before applying the product.**
2. Using a plastic watering can, cover the cement slurry with SLURRY REMOVER. Work in small sections.
3. Lightly scrub.
4. Rinse immediately and thoroughly.

**Product should not sit on the surface more than a few seconds.**

Polymeric sand haze on concrete pavers or slabs:

1. If application is done on pavers with new polymeric sand joints, **wait 30 days before applying the product.**
2. Work in small sections; no more than 50 sq. ft.
3. Using a plastic watering can, cover the area with SLURRY REMOVER.
4. Lightly scrub.
5. Rinse immediately and thoroughly.
6. Move on to the next section.

**Product should not sit on the surface more than a few seconds.**

**IMPORTANT:** DO NOT let product dry on the surface. If product dries on the surface, reapply product, lightly scrub and rinse immediately and thoroughly.

**TIP:** To improve efficiency on large areas, 3 persons are recommended to apply the product. One person should spray (pour) the product while another is scrubbing and a third is rinsing.

**COVERAGE**

1 gal. of concentrated product clean up to 600 sq. ft. Coverage will depend on surface condition and product dilution.

**PACKAGING**

Product Code	Pro Size	Units per box	Units per pallet
60101231 (221-553)	1 gal.	4	144
60200413 (221-556)	5 gal.	-	48

**WARNING**

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit [www.techniseal.com](http://www.techniseal.com) or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

**KEEP OUT OF REACH OF CHILDREN**

**TRANSPORT**

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit [www.techniseal.com](http://www.techniseal.com) or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

## LIMITED WARRANTY

---

LIMITED WARRANTY: Manufacturer, having no control over the use of the materials, does not guarantee finished work. Replacement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 4 sq.ft. (0.4 m<sup>2</sup>). This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty made above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods and implied warranty of fitness of goods for any particular purpose.