



Weatherproof Sealant

UPDATE

January 10th, 2023

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com

Canada and U.S.A.: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Adheres to most material: shingles, sheet metal, aluminum, copper, glass, wood and PVC

PROPERTIES

- Seals instantly, even under water, snow and ice
- Adheres to most material
- High Elasticity Formula

DESCRIPTION

Weatherproof Sealant from Techniseal® adheres to almost any surface: asphalt shingles, sheet metal, aluminium, copper, glass, wood and PVC, found on a sloped roof. It is also compatible with gutters and similar structures. Highly recommended before the application of Elastomeric Roof Coating from Techniseal®.

Not compatible with polystyrene foam. Not resistant to solvents.

DIRECTIONS

Ready to use • Do not dilute • Remove all dirt and debris • With a brush or a rubber spatula, apply one thick coat perpendicular to the crack • For cracks wider than 5 mm; following the first application and while still fresh, apply fiberglass fabric, then apply a second coat a few days later.

PACKAGING

Colour	Product code	Retail Size	Units per pallet	Units per box
Clear	70978066 (140-701)	300 ml tube	1200	20

WARNING

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

TRANSPORT

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

LIMITED WARRANTY

Since it has no control over surface preparation and product application, Techniseal® can not guarantee the results. Techniseal warranty is limited to the replacement of product. A proof of purchase will be required for any claim. Note: User should have an up-to-date technical data sheet handy (techniseal.com) and make sure that this product meets his or her needs by carrying out a test under anticipated conditions of use.