



Wood Cleaner

UPDATE

February 28, 2023

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: techniseal.com
Canada and U.S.A.: dial 1 800 465-7325
Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Bare, pressure-treated, painted or stained wood, etc.
- Decks, fences, pergolas, balconies, sidings, window frames, shingles, cornices, etc.

PROPERTIES

- Restores wood to its original appearance
- For decks, fences, siding, etc. (bare, stained, painted or varnished wood)
- Dislodges mildew, ground-in dirt and grease (barbecue)

DESCRIPTION

Techniseal[®] Wood Cleaner is a powder concentrate to be dissolved in water. It restores wood to its original appearance by removing its greyish or blackish shade. It dislodges mildew, ground-in dirt and grease (barbecue). On bare wood, it ensures proper penetration of Techniseal[®] Wood Stains & Sealers. On painted, stained or varnished surfaces, it reduces the gloss of the old coating, thus ensuring proper adhesion of the new finish.

DIRECTIONS

BEFORE YOU BEGIN

- Cover adjacent surfaces that are not to be treated. • **ALWAYS TEST** on a small hidden area (0.4 m² or 4 sq. ft.) to ensure results meet your expectations (see warranty). • **Do not** use near waterways, lakes and rivers.

DILUTION

In a watering can, dissolve in warm water at the rate of 15 to 45 ml per liter of water, or 5 to 10 ml per liter of water if solution is applied to new or less than one year old cedar. Makes 34 litres of solution.

APPLICATION

Using a watering can, cover the surface and let work for 15 minutes. Scrub the surface along the wood grain pattern, **taking care not to let product dry**; rinse thoroughly with a water jet. Keep rinse water from reaching the sewers. Repeat if necessary.

Note: For easier, quicker and more effective rinsing, use a pressure water jet (500 to 1,000 lb./sq. in. (3,500 to 7,000 kPa)). This method also allows you to skip scrubbing.

COVERAGE

850 g of diluted powder clean 15 to 39 m² (170 to 425 sq. ft.). Coverage will depend on the wood condition.

STORAGE

Store in cool and dry place.

PACKAGING

Product Code	Retail Size	Units per box	Units per pallet
60102038 (144-500)	850 g	12	540

WARNING

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

TRANSPORT

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

LIMITED WARRANTY

Having no control over the use of the products, Techniseal® does not guarantee finished work. Replacement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use, and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 4 sq. ft. This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty described above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods, and implied warranty of fitness of goods for any particular purpose.