



A FASTER & CLEANER WAY  
WITH TECHNISEAL'S SYSTEM  
FOR PORCELAIN PAVERS



### NextGel PORCELAIN PAVER JOINTING SAND

COLOR	CODE	WEIGHT
White Pearl	141000066	25 lbs
Black Onyx	141000065	25 lbs
Grey Moonstone	141000064	25 lbs
Beige Agate	141000067	25 lbs

#### CAUTIONS SPECIFIC TO PORCELAIN PAVERS

- Mechanical compaction should be done until joint is saturated. Several passes may be required.
- Porcelain pavers should never be installed with a porcelain to porcelain contact.

341-444 (02/2026)

Contact your local Techniseal® representative, visit [techniseal.com](http://techniseal.com) or dial 1 800 465-7325 for more details.



## NextGel PORCELAIN PAVER JOINTING SAND

A FASTER & CLEANER SOLUTION  
FOR GROUTING PORCELAIN PAVERS



- INNOVATIVE GROUT ALTERNATIVE
- NO MIXING REQUIRED
- FAST & EASY
- COLOR CONSISTENT EFFLORESCENCE-FREE



Residential & Commercial Use

Convenient 25 lb bag covers 100 sq. ft.

For joints from 1/16" to 1/2"



Innovative grout alternative  
Color consistent - Efflorescence-free  
No mixing required, fast and easy

FOR JOINTS FROM 1/16" TO 1/2"



**SPECIFICALLY  
DESIGNED** for your  
**PORCELAIN PROJECTS**  
with **Ultra-Clean Technology**

# NextGel™ PORCELAIN PAVER JOINTING SAND



**1**  
**SPREAD  
THE SAND**

- Spread product evenly on a small surface. Using the street broom, fill joints completely. Spread sand over short distances.



**2**  
**COMPACT  
THE SAND**

- Pass the paver roller compactor over the entire surface to compact the sand.
- Add more product and spread to fill joints again.



**3**  
**ACTIVATE  
BY WATERING**

- Using the water sprayer, starting from bottom of the slope, quickly water the joints of a 100 sq. ft. section\* to set the sand (10 to 15 seconds).
- Immediately wet the same section where joints have absorbed more water.
- Check for water accumulation at the surface of the jointing sand as a cue to stop watering. Wait until there is no free water at the surface of the joint and verify the depth of activation.

## NECESSARY TOOLS

- Street broom with semi-rigid bristles.
- Paver roller compactor.
- Hand tamper may be needed in restricted areas where using heavier equipment may not be possible.
- Leaf blower.
- Handheld or backpack sprayer for precise watering of the joints.



CONTROLLED TESTING IN TECHNISEAL R&D LAB  
Techniseal  
**NextGel™ PORCELAIN**  
PAVER JOINTING SAND



COMPETITOR  
JOINTING SAND




If NextGel™ PORCELAIN PAVER JOINTING SAND is activated at 75% or more of its depth stop watering. If activated at less than 75%, water for an additional 5 seconds and check again after 30 seconds.

\*NextGel™ PORCELAIN PAVER JOINTING SAND is fast to activate. It is very easy to overwater installations with large tiles. Carefully track the watering time during the activation process.



AVAILABLE IN:



White  
Pearl



Black  
Onyx



Grey  
Moonstone



Beige  
Agate

