



SMARTSAND® NextGel™

POLYMERIC SAND
For Interlocking Concrete Pavers

**The Smart
Choice for
your Everyday
Installations**



- Ideal for residential projects
- Designed for optimal jointing of interlocking pavers
- Ideal for joints from 1/16" - 1/2" with intersecting spaces up to 1"
- For pedestrian and low-traffic areas such as driveways, walkways, patios, etc.

Manufactured with the NextGel™ technology, SMARTSAND® NextGel™ is a cost-effective alternative to HP NextGel™, when high-performance sand is not required. Its "quick activation" formula makes it the best choice for everyday installations.

NECESSARY TOOLS:



Street Broom



Plate Compactor /
Roller Paver Compactor



Hand Tamper



Leaf Blower



Garden Hose & Hose Gun

3 EASY STEPS:



TIPS:

- It is imperative to allow the installation to **dry completely** before installing the new jointing product.
- Temperature must be above 32 °F (0 °C) for 48 hours following installation.
- Allow a **minimum of 24-48 hours** in dry conditions (depending on the overall temperature and humidity).
- A wet foundation or surface will cause the activation of the jointing product before compaction and activation. It may also clog the sides of the stones and prevent the products from filling the entire joints in depth.
- On textured pavers, use a leaf blower to blow surface water into the joints. This will remove any remaining sand and polymer residue, which will prevent hazing.
- Refer to the complete Technical Data Sheet on techniseal.com.

IMPORTANT:

Polymeric sand curing time after installation: **30 days**. Ensure that joint has hardened before cleaning and sealing the surface. Depending on climate and type of installation, typical recommended wait time is a minimum of 7 days after installation and may take up to 30 days.

COVERAGE: Depends on paver type and joint width. (Please see our product calculator on our website.)

MAINTENANCE:

ORGANIC WASTE MANAGEMENT

Prevent organic waste from accumulating on paver installations by regularly clearing the surface of any debris or residue using a street broom or a leaf blower. In the summer, remove cut grass from the pavers after mowing the lawn. In the fall, regularly pick up dead leaves and broken branches.

WATER AND MOISTURE MANAGEMENT

If you water your lawn with an automated sprinkler system, make sure it is calibrated properly to prevent water accumulation on the surface of paver installations, especially in shaded areas. When cleaning the pavers, don't aim the water jet directly into the joints, avoid overwatering the surface. Watering gun nozzles should be used instead of pressure washers.

Consider repositioning your roof gutter downspouts, or use a disperser, to avoid excessive water runoff during bad weather.

Polymeric Sand	Product Code	Color	Size	Units per pallet
	40101235	Ash Grey	50 lbs (bag)	56
	40100235	Atlantic Tan	50 lbs (bag)	56
	40100505	Cali Tan	50 lbs (bag)	56
	40100098	Carolina Granite	50 lbs (bag)	56
	40101219	Granite	50 lbs (bag)	56
	40100094	Southern Granite	50 lbs (bag)	56
	40101218	Tan	50 lbs (bag)	56
	40101220	Urban Grey	50 lbs (bag)	56



Techniseal® Jointing products contribute to LEED credits, based on the use of regional and recycled materials.



Visit techniseal.com or dial 1-800-465-7325 for more details.

