# 

# INTRODUCING



## NEXTGEL<sup>™</sup> FORTIFIED HARDSCAPE CONCRETE EDGING


Techniseal\*

FORTIFIED HARDSCAPE CONCRETE EDGING

T & EASIEST

permeable installations

form finish orkability



- FASTEST & EASIEST installation on the market
- More than 10% extra coverage
- Ideal for permeable installations
- Smooth, uniform finish
- Maximum workability
- Dispersible reinforcement fibers



#### EDGE BOND<sup>™</sup> is the perfect choice for:

- Traditional, open graded or permeable installations
- NEXTBASE<sup>™</sup> foam panel installations
- Concrete overlay installations
- Concrete pavers, wet-cast pavers, clay pavers, natural stone, slabs, textured pavers
- Commercial, residential and public projects
- Pedestrian and vehicular use



NextGel<sup>™</sup> is a revolutionary technology that radically transforms and improves the properties and behavior of jointing products and additives.

## **DIRECTIONS FOR USE:**

## **NECESSARY TOOLS:**

- Measuring cup
- Wheelbarrow or mortar pan
- Shovel
- Hand trowel, preferably 4" wide
- · Rag, sponge or small vinyl brush for cleaning

#### **BEFORE YOU BEGIN**

• Installation of EDGE BOND<sup>™</sup> is recommended to be done right before mechanical compaction of the hardscape material.



### **INSTALLATION**

- Remove bedding layer (sand or chips) on the entire perimeter of the installation.
- Empty contents of EDGE BOND<sup>™</sup> into a wheelbarrow.
- Add 2.5 quarts of clean potable water per 50 lb bag of EDGE BOND<sup>™</sup>. Mix until blend is uniform.
- Using a shovel, place the EDGE BOND<sup>™</sup> in the trench created.
- Using a hand trowel, shape EDGE BOND<sup>™</sup> into a triangular profile at a 30° to 45° angle.
- Complete your installation by back filling with topsoil, mulch or decorative stone over the EDGE BOND<sup>™</sup> edging.

Item #:

Col



#### **INSTALLATION TIPS:**

- 0.625 US gallon = 2.5 guarts = 10 cups = 80 fl.oz. = 2.37 liters
- Temperature must be above 40°F (4°C) for 48 hours following installation.
- Sprinkler system must be turned off.
- Do not mix product with cement, sand or any other material.
- · Ready-to-use simply add water
- Paintable or sealable if used as decorative edging
- Freeze and thaw resistant
- Alternative to plastic edging and spikes
- Additional strength and stability (when compared to traditional plastic edging)



Color:	Grey
Packaging:	50 lb bag (56 bags per pallet)
	www.

70975209



COVERAGE For a 50 lb bag : 16 - 20 linear feet The amount required will depend on the shape and size of the edging.

