

INTRODUCING

EDGE BOND™

Powered with NextGel

NEXTGEL™ FORTIFIED HARDSCAPE CONCRETE EDGING



EDGE BOND™, with maximum workability, is the perfect alternative to plastic edging and spikes.

- FASTEST & EASIEST installation on the market
- More than 10% extra coverage
- Ideal for permeable installations
- Smooth, uniform finish
- Maximum workability
- Dispersible reinforcement fibers



EDGE BOND™ is the perfect choice for:

- Traditional, open graded or permeable installations
- NEXTBASE™ foam panel installations
- Concrete overlay installations
- Concrete pavers, wet-cast pavers, clay pavers, natural stone, slabs, textured pavers
- Commercial, residential and public projects
- Pedestrian and vehicular use



NextGel™ is a revolutionary technology that radically transforms and improves the properties and behavior of jointing products and additives.

DIRECTIONS FOR USE:

NECESSARY TOOLS:

- Measuring cup
- Wheelbarrow or mortar pan
- Shovel
- Hand trowel, preferably 10 cm (4") wide
- Rag, sponge or small vinyl brush for cleaning

BEFORE YOU BEGIN

- Installation of EDGE BOND™ is recommended to be done right before mechanical compaction of the hardscape material.



INSTALLATION

- Remove bedding layer (sand or chips) on the entire perimeter of the installation.
- Empty contents of EDGE BOND™ into a wheelbarrow.
- Add Add 2,37 L (2.5 quarts US) of clean potable water per 22.7 kg (50 lb) bag of EDGE BOND™. Mix until blend is uniform.
- Using a shovel, place the EDGE BOND™ in the trench created.
- Using a hand trowel, shape EDGE BOND™ into a triangular profile at a 30° to 45° angle.
- Complete your installation by back filling with topsoil, mulch or decorative stone over the EDGE BOND™ edging.



INSTALLATION TIPS:

- 2.37 liters = 0.625 US gallon = 2.5 quarts US = 10 cups = 80 fl.oz.
- Temperature must be above 4°C (40°F) for 48 hours following installation.
- Sprinkler system must be turned off.
- Do not mix product with cement, sand or any other material.

- Ready-to-use - simply add water
- Paintable or sealable if used as decorative edging
- Freeze and thaw resistant
- Alternative to plastic edging and spikes
- Additional strength and stability (when compared to traditional plastic edging)



Item #: 70972432
Colour: Grey
Packaging: 22.7 kg (50 lb) bag
(56 bags per pallet)



COVERAGE 4.9 to 6.1 linear meters per 22.7 kg bag (16 to 20 linear feet per 50 lb bag). The amount required will depend on the shape and size of the edging.

